

B4 LATE MODEL /STREET STOCK

- *Only chassis allowed is the standard RTR chassis**
- *No modifications may be made to chassis, must be raced in stock form**
- *RPM front bumper is allowed**
- *Any shock oil, springs, spacers or body mount you choose**
- *You may add weight any place on the vehicle, but you may not modify the chassis or suspension in any way including removing weight**
- *Both front and rear suspension systems must remain in stock form**
- *All cars must use the 25 degree castor blocks and 3 degree rear toe blocks**
- *Wheels spacers may be used**
- *Ball differentials are not allowed**
- *All replacement parts must be a direct replacement from the manual**
- *No modification may be made to the steering system, original factory parts only**
- *Original ESC must be used**
- *Servo may be changed to any servo less than \$35.00 street price**
- *You may use any Tx and Rx you choose**
- *Reedy 3300kv motor must be used**
- *Any 2 cell 5000mah 20c hard case lipo**
- *81 tooth spur and 21 tooth pinion must be used in limited class**
- *81 tooth spur and up to 23 tooth pinion may be used in pro class**
- *Custom Works Street Trac or Losi Mini 8ight tires losb1955-56**
- *No AVC, gyros or traction control.**
- *3" max height on rear spoiler**
- *3 ½" max length on side dams. Side dams can not exceed the max height of spoiler**
- *Side dams must be triangle shape**

IF IT'S NOT ON THIS RULES SHEET IT IS NOT LEGAL!!!!

